

# 90° SWEEPING BEND (COMP-001-ABS-R25 - 25mm)



## EN

Designed for changing the direction of a pipe run through 90 degree's on an aspirating smoke detection pipe network. Pipe is designed for aspirating fire detection only.

### Installation Instructions:

Use the correct solvent Plusbond 3019. Do not paint. Keep pipe clean and free from dust. Do not install in direct sunlight. Only install with approved pipe. Do not use solvents to clean, only soapy water.

## TR

Bir aspirasyonlu duman algılama boru ağında 90 derecelik bir boru akışının yönünü değiştirmek için tasarlanmıştır. Boru sadece aspirasyonlu yangın algılama için tasarlanmıştır.

### Kurulum Talimatları:

Doğru solvent Plusbond 3019 kullanın. Boya yapmayın. Boruyu temiz ve tozsuz tutun. Doğrudan güneş ışığı altında montaj yapmayın. Sadece onaylı boru ile monte edin. Temizlemek için solvent kullanmayın, sadece sabunlu su kullanın.

<b>OPERATING TEMPERATURE:</b> -40°C to 70°C	<b>DIAMETER TOLERANCE:</b> +/- 0.15mm	<b>OUTSIDE DIAMETER:</b> 32.1mm	<b>WEIGHT:</b> 32 Grams
<b>PIPE COLOUR:</b> Red	<b>WALL THICKNESS:</b> 4.4mm	<b>INSIDE DIAMETER:</b> 25mm	

