

# THREADED TEE TEST POINT (COMP-0039-ABS-R25 - 25mm)



## EN

This component is used when the system needs to be smoke tested. The threaded plug is removed, which allows the smoke generator to gain access to the system. Simply replace after use.

### Installation Instructions:

Use the correct solvent Plusbond 3019. Do not paint. Keep pipe clean and free from dust. Do not install in direct sunlight. Only install with approved pipe. Do not use solvents to clean, only soapy water.

## TR

Bu bileşen, sistemin duman testine tabi tutulması gerektiğinde kullanılır. Duman jeneratörünün sisteme erişimini sağlayan dişli tapa çıkarılır. Kullanımdan sonra değiştirmeniz yeterlidir.

### Kurulum Talimatları:

Doğru solvent Plusbond 3019 kullanın. Boya yapmayın. Boruyu temiz ve tozsuz tutun. Doğrudan güneş ışığı altında montaj yapmayın. Sadece onaylı boru ile monte edin. Temizlemek için solvent kullanmayın, sadece sabunlu su kullanın.

**PART NO.:**  
COMP-0039-ABS-R25

**PIPE COLOUR:**  
Red

**OPERATING TEMP:**  
- 40 c to 70 c'

**WEIGHT:**  
29.6 g

**FITTINGS COLOUR:**  
Red

**DIAMETER  
TOLERANCE:**  
+ / - 0.15mm'

**WALL THICKNESS:**  
2mm

